

BRAVO

By **Tech Quality Co.,Ltd.**



Leak Test Chamber

The **LTC -SQ Series** Leak Test Chamber Leak detection system for packages with bubble test. LTC EASY features the detection even of the smallest leaks.

The package is placed into a chamber filled with water, the head space above the water-level is evacuated using a vacuum pump system. The package immersed in water inflates, any leak and the location of the leak is identified by a stream of bubbles

Feature

- ใหม่ตู้ทดสอบทรงเหลี่ยมทำให้มองเห็นรอยรั่วชัดเจนยิ่งขึ้นรอบทิศทาง
- แข็งแรงกว่าด้วยอะคริลิกหนาถึง 30 มิลลิเมตร
- แม่นยำยิ่งขึ้นด้วยชุด Panasonic Vacuum meter จากญี่ปุ่น
- ชุดนับเวลาคอนคุณภาพสูงจาก PANASONIC
- ทนทานกว่าด้วย AIRTEC Vacuum Pump จาก USA
- no calibration required
- low maintenance
- **ที่สำคัญราคาถูกลงกว่า Low Cost**

According to Standard test method

ASTM D3078- Standard Test Method for Determination of Leaks in Flexible Packaging by Bubble Emission

ASTM D4991- Standard Test Method for Leakage Testing of Empty Rigid Containers by Vacuum Method

ASTM D6653- Standard Test Methods for Determining the Effects of High Altitude on Packaging Systems by Vacuum Method

Specification

LTC SQ30 Inside Chamber Diameter : W300xL300xH300 mm

LTC SQ45 Inside Chamber Diameter : W450xL450xH300 mm

Option chamber size : Customer request

Acrylic thickness : 30 mm

"PANASONIC" Digital Timer : 0-9999 Min

"PANASONIC" Japan Digital Vacuum meter

"AIRTEC" USA Vacuum Pump 0.32Kw

Maintenance free operation

Flow rate : 66 L/min

Maximum Vacuum : 740 mmHG (93KPA)

Power 220Vac

Ordering Information

Tech Quality Co.,Ltd.

2/13 Sukapiban 2 Rd., Pravet , Pravet, Bangkok
10250 Thailand

Tel : +662 328 6878 (Auto)

Fax : +662 328 6818

www.tech-quality.com

email: info@tech-quality.com